



NOTES:
 1. PACKAGE CONFORMS TO JEDEC MS-011, VARIATION AC.
 2. DIM AND TOL CONFORM TO ASME Y14.5-2009.
 3. ALL DIM ARE IN INCHES.
 4. D AND E1 DIMENSIONS FOR PLASTIC PACKAGES DO NOT INCLUDE MOLD FLASH OF PROTRUSIONS. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.010 INCH (0.25 MM).

SYMBOL	MIN	MAX	SYMBOL	MIN	MAX
A	0.165	0.175	E	0.600	0.625
A1	0.015	-	E1	0.540	0.560
A2	0.145	0.155	eB	0.640	0.660
A3	0.07 REF		L	0.115	0.200
b	0.014	0.022			
b1	0.030	0.070			
D	1.980	2.095			
D1	0.005	-			
e	0.100 BSC				



TITLE		
40 LEAD PDIP-600 mils		
DWG. NO.:	40 Lead PDIP-600	REV A
DO NOT SCALE	File Name: 40L-PDIP-600.PDF	SHEET 1 of 1

ALL INFORMATION CONTAINED HEREIN IS THE PROPERTY OF QPTECHNOLOGIES AND IS CONSIDERED PROPRIETARY AND SUBJECT TO RETURN UPON DEMAND. ACCEPTANCE AND RETENTION HEREOF SIGNIFIES AGREEMENT BY THE RECIPIENT THAT THE INFORMATION WILL NOT BE DISCLOSED TO OTHERS NOR USED CONTRARY TO THE INTEREST OF QPTECHNOLOGIES WITHOUT PRIOR WRITTEN PERMISSION